

TECHNICAL DATA

Fluke 9040 Phase Rotation Indicator



Key features

- 3 phase indication
- Indication of phase rotation
- Clear LCD display
- No battery required

Product overview: Fluke 9040 Phase Rotation Indicator

Phase rotation indicator with high voltage capability for industrial applications

The Fluke 9040 is effective for measuring phase rotation in all areas where three phase supplies are used to feed motors, drives and electrical systems. The Fluke 9040 is a rotary field indicator and can provide clear indication of the 3 phase via an LCD display and the phase rotation direction to determine correct connections. It allows rapid determination of phase sequence and has a voltage (up to 700 V) and frequency range suitable for commercial and industrial applications. The included test probes have a variable clamping range for safe contact, also in industrial sockets.

Specifications: Fluke 9040 Phase Rotation Indicator

Technical Specifications	
Voltage Range	40-700 V



Frequency Range	15-400 Hz	
Operating Timer	Continuous	
Environmental Specifications		
Operating Temperature	0°C to 40°C	
Dust/Water Resistance	IP 40	
Safety Specifications		
Electrical Safety	EN 61010,	
	EN 61557-7	
Overvoltage category	CAT III, 600 V	
	CAT IV, 300V	
Mechanical and General Specifications		
Size	124 x 61 x 27 mm	
Weight	200 g	
Power supply	From unit under test	
Warranty	2 years	



Ordering information



Fluke 9040

Fluke 9040 Phase Rotation Indicator

Includes:

- 3 self-retaining test probes (black)
- alligator clip
- user manual



Fluke. Keeping your world up and running. ${\it \$}$

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2024 Fluke Corporation. Specifications subject to change without notice. 03/2024

Modification of this document is not permitted without written permission from Fluke Corporation.