



8860 SERIES (1.5 kW)

Models	8860	8861	8862 & 8862 D	8863	8864
Power Rating	1500 W continuous				
Frequency Range and VSWR	DC to 1 GHz at 1.1 max., (1.065 max., 470-860 MHz for "D" Model) 1 GHz to 2 GHz at 1.25 max.				
Ambient Temperature Range	-40°C to +45°C				
Connector	QC-LC(F)	1 5/8" Unflg.	1 5/8" EIA flg.	3 1/8" Unflg.	3 1/8" EIA flg.
Operating Position	Horizontal only				
Load Coolant	1.5 gal. (5.68 liters) silicone oil				
Finish	Gray powder coat				
Nominal Size	17 1/8" L x 7 1/2" W x 13 1/8" H, (445 mm x 184 mm x 333 mm)	17 7/8" L x 7 1/2" W x 13 1/8" H, (454 mm x 184 mm x 333 mm)	17 1/8" L x 7 1/2" W x 13 1/8" H, (445 mm x 184 mm x 333 mm)	18 5/8" L x 7 1/2" W x 13 1/8" H, (473 mm x 184 mm x 333 mm)	19 1/2" L x 7 1/2" W x 13 1/8" H, (495 mm x 184 mm x 333 mm)
Weight	30 lbs. (13.6 kg)	31 lbs. (14.1 kg)	31 lbs. (14.1 kg)	32 lbs. (14.5 kg)	32 lbs. (14.5 kg)

